



Product Data

BP Visco 3000 A3/B4 10W-40

Cleanguard Engine Protection Technology

Description

BP Visco 3000 A3/B4 10W-40 is a premium quality part synthetic engine oil that utilises Cleanguard Engine Protection Technology to keep your engine cleaner for longer.

Your car runs better if the engine is kept clean.

BP Visco series Cleanguard technology keeps your engine clean by preventing dirt such as carbon and sludge from sticking to sensitive engine parts and the vital oil ways.

Cleanguard technology slows down the formation of carbon and sludge and wraps up dirt so that they can not stick to the engine.

Application

BP Visco 3000 A3/B4 10W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, API SL/CF or earlier specification 10W-40 lubricant.

BP Visco 3000 A3/B4 10W-40 is approved for use in VW group vehicles that require a VW 501 00 / 505 00 specification 10W-40 lubricant and Mercedes vehicles that require a MB-Approval 229.1 specification 10W-40 lubricant.

Advantages

BP Visco 3000 A3/B4 10W-40 offers the following benefits:

- Improved engine cleanliness.
- Advanced protection for normal driving conditions.
- Reduced oil consumption.

Typical Characteristics

Name	Method	Units	BP Visco 3000 A3/B4
Density @ 15C, Relative	ASTM D4052	g/ml	0.8631
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.55
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6730
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	97.000
Viscosity Index	ASTM D2270	None	156
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	1.000

Product Performance Claims

ACEA A3/B4
API SL/CF
Meets Fiat 9.55535-D2
MB-Approval 229.1
VW 501 01 / 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 3000 A3/B4 10W-40

17 Jun 2013

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.bp.com/uk