Product information

Synthoil Race Tech GT1 10W-60



Description

Fully synthetic high-performance motor oil for extreme operating conditions. With wide-band viscosity 10W-60 and high temperature stability. Optimizes engine performance. For immediate lubrication at cold start and very good wear protection.

Properties

- outstanding engine cleanliness
- miscible with all commercially available motor oils
- high lubrication reliability
- tested for catalytic converters
- optimum stability to aging
- optimum lubrication in extreme operating conditions
- rapid oil delivery at low temperatures
- extremely low oil consumption
- extremely low evaporation loss



ACEA A3 • ACEA B4 • API SL

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-H3

Technical data	
SAE class (engine oils)	10W-60 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	168 mm²/s ASTM D 7042-04
Viscosity at 100 °C	24,0 mm²/s ASTM D 7042-04
Viscosity at -30°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25°C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	174 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016



Technical data

i o o i i i i o o i i i o o o o o o o o	
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

For gasoline and diesel engines with and without turbocharging. Especially suitable for extreme engine requirements and racing.

PI 29/08/11/2018

Application

Note the vehicle and engine manufacturers' operating instructions.

Available pack sizes

1 l Canister plastic	8908 BOOKLET
1 l Canister plastic	20911 JP
5 l Canister plastic	8909 BOOKLET
5 l Canister plastic	20912 JP
20 l Canister plastic	1392 D-GB-I-E-P
20 l Canister plastic	20933 JP
60 l Drum sheet metal	1393 D-GB
205 l Drum sheet metal	1394 D-GB
1000 l Container	1772 D-GB
1 l Bulk goods	1399 D-GB

Flash point

Evaporation loss (Noack)

5,3 %

246 °C

CEC-L-40-A-93

DIN ISO 2592

Product information

PI 29/08/11/2018

LIQUI MOLY

Synthoil Race Tech GT1 10W-60

Our information is based on thorough research and may be considered reliable, although not legally binding.