



Mobil Ultra 10W-40

Mobil Passenger Vehicle Lube, Ukraine

Premium Quality Multigrade Passenger Vehicle Engine Oil

Product Description

Mobil Ultra 10W40 is a premium quality motor oil for many types of gasoline and Diesel vehicles.

Features and Benefits

Mobil Ultra 10W-40 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering very high performance and engine protection under a variety of driving conditions. Mobil Ultra 10W-40 reduces engine wear with excellent high and low temperature performance. This oil is also approved by leading car manufacturers.

Applications

Mobil Ultra 10W-40 can be used in a variety of passenger vehicles , light trucks and vans, and for anyone seeking a dependable super premium quality product.

Specifications and Approvals

Mobil Ultra 10W-40 meets or exceeds the requirements of the following industry specifications:	
API SL, SJ	X
ACEA A3/B3	X

According to ExxonMobil, Mobil Ultra 10W-40 is of the following quality level:	
API CF	X

According to ExxonMobil, Mobil Ultra 10W-40 is of the following quality level:	
MB-Approval 229.1	X

Typical Properties

Mobil Ultra 10W-40	
SAE Grade	10W-40
Viscosity, ASTM D 445	
cSt @ 40° C	95.7
cSt @ 100° C	14.5
Viscosity Index, ASTM D 2270	157
Sulphated Ash, wt%, ASTM D 874	1.3

Mobil Ultra 10W-40	
HTHS Viscosity, mPa•s @ 150° C ASTM D4683	3.9
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	223
Density @15° C kg/l, ASTM D 4052	0.875

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Running Tiger design and Ultra are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

06-2018

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.