

Shell Helix Ultra I 5W-30

Fully synthetic motor oil - advanced formulation for high performance engines



Shell Helix Ultra I uses active cleansing technology to help high-performance engines operate at maximum efficiency. It helps to reduce engine friction to provide enhanced fuel economy.

Proud Drivers Choose Shell Helix

Main Applications

 Shell Helix Ultra I's fully synthetic formulation is designed to
VW 502.00/505.00 provide professional workshop and fleet operators with a high performance, versatile motor oil that is approved by leading European OEMs.

Specifications, Approvals & Recommendations

- API SL
- ACEA A3/B3, A3/B4
- BMW LL-01

- MB-Approval 229.5/226.5
- Renault RN 0700, RN 0710

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra I 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.77
Kinematic Viscosity	@40°C	cSt	ASTM D445	66.34
Viscosity Index			ASTM D2270	176
Dynamic Viscosity	@-30°C	cP	ASTM D5293	5 000
MRV	@-35°C	cP	ASTM D4684	12 800
Density	@15°C	kg/m³	ASTM D4052	841
Flash Point		°C	ASTM D92	237
Pour Point		°C	ASTM D97	-39

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

· Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on health and safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained

from http//epc.shell.com

· Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.