

XADO Atomic Oil

0W-30 SL/CF

Easy-flowing synthetic oil of an extra class. Manufactured on the basis of complex synthetic base oils containing esters and polyalphaolefins. Contains atomic REVITALIZANT®.

Application temperature range

-35 °C — **+45 °C**



Advantages

- Ensures faultless operation of gasoline, LPG and diesel engines of passenger cars in all operation modes; indispensable for adherents of a confident and dynamic driving style.
- Perfectly suits for modern multivalve turbocharged engines including those with intercooling of forced air.
- Especially recommended for engines with extended oil change intervals; retains its unique protective properties even under conditions of extended service intervals.
- The best oil for engines of American vehicles including land rovers where easy-flowing oils (with low high-temperature viscosity SAE 30) are applied.
- Possesses strong adhesion (adherence), i.e. there is always a thin protective oil film on lubricated parts; the oil does not trickle down into the crankcase to the full extent.
- Due to its high fluidity rate the oil possesses excellent energy-saving properties, thus considerably reducing fuel consumption.
- Even at the lowest temperatures (up to – 35 °C) the oil reaches and lubricates all parts very quickly and makes the engine start extremely easy.
- Accurately maintains an optimal pressure in the lubricating system.
- Keeps the engine perfectly clean.

1L Art. XA 20101	4L Art. XA 20201	5L Art. XA 20301	20L Art. XA 20501
60L Art. XA 20601	200L Art. XA 20701		

Packaging: 1 to 5 L — can; 20 L — bucket;
60 and 200 L — barrel.

Operational properties

Specifications:

SAE 0W-30

ACEA A3/B4

API SL/CF



The oil is officially licensed by **American Petroleum Institute (API)** for its compliance with the highest requirements to oils for gasoline engines of passenger cars (**API SL**).

Volvo 95200356

VW 502 00/505 00

Renault RN0710/0700

MB 229.5/229.3