

XADO Atomic Oil

5W-40 SM/CF Eco Drive

Ultra modern synthetic motor oil of the API SM generation. Contains atomic REVITALIZANT®.



Application temperature range

-30 °C — **+45 °C**

Advantages

- A perfect oil for modern high-powered engines including multivalve and turbocharged ones and those with intercooling of forced air.
- Manufactured using mid SAPS technology; ensures extended service life span for catalyst converters and particulate filters.
- Meets the requirements of the new European quality standard – ACEA C3 (oils of the highest performance category with medium contents of sulfated ash, sulfur and phosphorus).
- Recommended for application in Euro 4 engines (MB, BMW).
- Suitable for diesel engines with a unit injector system (Pumpe-Düse). Meets the requirements of VW 505 01, Ford M2C-917-A.
- The oil is distinguished by its highest level of performance properties and provides the highest grade of protection and reliable operation of engines.
- This is a Longlife oil, it is used in engines with extended oil change intervals.
- Extends the service life span of additional exhaust gas purification units.
- Keeps the engine perfectly clean.

1 L

Art. XA 20122/
Art. XA 24122

4 L

Art. XA 20222

5 L

Art. XA 20322

20 L

Art. XA 28522

60 L

Art. XA 20622

200 L

Art. XA 20722

Packaging: 1 to 5 L — can; 20 L — bucket;
60 and 200 L — barrel.

Operational properties

Specifications:

SAE 5W-40

ACEA C2/C3

API SN/SM/CF

GM dexos2

BMW Longlife-04

VW 502 00/505 01

MB 229.31/226.5



The oil is officially licensed by **American Petroleum Institute (API)** for its compliance with the highest requirements to oils for gasoline engines of passenger cars (**API SM**).

Porsche A40

Ford WSS-M2C917-A

Renault RN0710/0700