

VERYLUBE

10W-40 SL/CI-4

Semi synthetic motor oil. Manufactured with use of base oils according to the hydrocracking synthesis technology.



Advantages

- Universal application in gasoline, diesel and LPG engines of passenger cars and trucks.
- Effective for modern engines: multi-valve, turbocharged (including those with exhaust gas recirculation system), with direct fuel injection etc.
- Meets the specifications and requirements of many car manufacturers for modern oils and therefore is an excellent solution for mixed vehicle fleets.
- Provides stable and reliable protective properties during the run-in period and by car operation.
- Provides an excellent protection and reliable lubrication of the engine, keeps it clean.

1 L

Art. XB 20164

4 L

Art. XB 20264

60 L

Art. XB 20664

200 L

Art. XB 20764

Packaging: 1 and 4 L — can; 60 and 200 L — barrel.

Requirements and specifications

Meets the requirements of the following specifications:

SAE 10W-40

ACEA A3/B4/E7

API SL/CI-4 Plus/CI-4/CH-4/CG-4/CF-4/CF

Global DHD-1

Allison C4

Cummins 20071/72/76/77/78

Meets the requirements of manufacturers:

VW 500 00/505 00

Renault (RVI) RLD-2

MB 228.3, 229.1

Mack EO-M Plus

Volvo VDS-2, VDS-3

MTU Type 2

MAN 3275

ZF TE-ML 02C/03A/04B/04C/07C