

VERYLUBE

15W-40 CI-4 Diesel

Special high-class motor oil for diesel engines.



Advantages

- Universal application for all types of diesel engines of passenger cars and trucks, as well as special overland equipment.
- Perfectly suitable for diesel engines with exhaust gas recirculation system and especially recommended for Euro III (II) diesel engines.
- Provides perfect protection of the turbocharger.
- Possesses significant reserve of operational properties and provides maintenance intervals of up to 100,000 km for Euro III engines.
- Reliably protects the engine operating on fuel with high sulfur content (S= up to 0.5 %).
- Keeps the engine clean, neutralizes soot contamination of oil.
- Guarantees reliable lubrication of the engine by intensive modes of operation and high temperatures.

60 L

Art. XB 23669

200 L

Art. XB 20769

Packaging: 60 and 200 L – barrel.

Requirements and specifications

Meets the requirements of the following specifications:

- SAE 15W-40
- ACEA A3/B4/E7
- API CI-4/CH-4/CG-4/CF-4/CF
- Global DHD-1
- JASO DH-1

Meets the requirements of manufacturers:

- DAF Long Drain
- Volvo VDS-3
- Deutz DQC-III-10 LA
- Volvo VDS-3
- Mack EO-N
- MB 228.51/226.9
- MTU Type 3 and 3.1
- Renault RXD, RLD-2, RGD
- Caterpillar 20076/77
- MAN M 3277, M 3477, M 3277 low ash for CRT, M 3271-1 (LPG & CNG engines)