

VERYLUBE 5W-40 SL/CF

High class synthetic motor oil.



Advantages

- Multigrade application in passenger cars and light trucks.
- Universal application in gasoline, diesel and liquefied petroleum gas (LPG) engines.
- Effective for modern engines: multi-valve, turbocharged (including those with exhaust gas recirculation system), with direct fuel injection etc.
- Quickly enters all the lubrication points and provides easy engine start at low temperatures (up to -30°C).
- Resistant to ageing, notable for the stable properties by long maintenance intervals (more than 15,000 km of run).
- Reliably lubricates friction parts of the engine, creates a solid and stable oil film by cold start and preserves it at high temperatures and under severe operating conditions.
- Keeps the engine clean and prevents soot and deposits formation.
- Due to the special viscosity properties, it is an energy-saving oil.
- Can be mixed with other synthetic and mineral motor oils.

1 L

Art. XB 20159

4 L

Art. XB 20259

60 L

Art. XB 20659

200 L

Art. XB 20759

Packaging: 1 and 4 L — can; 60 and 200 L — barrel.

Requirements and specifications

Meets the requirements of the following specifications:

SAE 5W-40

ACEA A3/B3/B4(08)

API SL/CF

Meets the requirements of manufacturers:

VW 502 00/505 00

Porsche A40

MB 229.3

BMW Longlife-01

GM-LL-B-025

**PSA B71 2294 In
Prog. (PSA Level 2)**

Renault RN 0700/0710