

# ZIC TOP

PCMO

## ULTIMATE ADVANCED PAO BASED FULLY SYNTHETIC ENGINE OIL FOR THE NEXT GENERATION

### FULLY SYNTHETIC

#### SPECIFICATIONS

- ACEA C3(5W-30), A3/B4(0W-40)
- Approved:
  - 5W-30: MB-Approval 229.51, VW 504 00/507 00, BMW LL-04, PORSCHE C30
  - 0W-40: VW 502 00/505 00



#### GENERAL CHARACTERISTICS

- Excellent wear protection for extended engine life
- Maximizes acceleration and performance in extreme driving conditions
- Outstanding sludge control to keep the engine clean
- Advanced fuel efficiency and oil durability

#### DESCRIPTION

ZIC TOP is an ultimate advanced 100% synthetic motor oil, newly launched as the flagship tier of ZIC. ZIC TOP is formulated with PAO base oil and ZIC's cutting-edge additive technology. ZIC TOP helps to extend your engine life by protecting from wear and corrosion. ZIC TOP also provides outstanding engine performance under the most severe conditions and keeps your engine clean and powerful.

#### RECOMMENDATIONS

- Recommended for Gasoline/Diesel/LPG engines

#### TYPICAL PROPERTIES

| SAE Grade                         | 5W-30          | 0W-40          |
|-----------------------------------|----------------|----------------|
| Density, g/cm <sup>3</sup>        | 0.8535         | 0.8540         |
| Kinematic Viscosity at 40°C, cSt  | 68.75          | 84.35          |
| Kinematic Viscosity at 100°C, cSt | 11.95          | 14.35          |
| Viscosity Index                   | 171            | 175            |
| Total Base Number (TBN), mgKOH/g  | 6.20           | 9.85           |
| Flash Point, °C                   | 230            | 230            |
| Pour Point, °C                    | -39            | -42            |
| CCS, cP                           | 6,100 (-30°C)  | 6,100 (-35°C)  |
| MRV, cP                           | 20,000 (-30°C) | 30,000 (-40°C) |
| HTHS Viscosity at 150°C, cP       | 3.60           | 3.70           |