

ZIC X7 FE

PCMO

**100% FULLY SYNTHETIC
PREMIUM ENGINE OIL FOR
FUEL EFFICIENCY**



FULLY SYNTHETIC

SPECIFICATIONS

- API SN/ILSAC GF-5
- Exceeds the requirements of dexos™1 (0W-30/5W-20)



GENERAL CHARACTERISTICS

- Strong oil film for wear resistance and engine protection
- Excellent fuel economy
- Low volatility for lower oil consumption and longer drain intervals
- Enhanced high and low temperature performance

DESCRIPTION

ZIC X7 FE is a premium fully synthetic motor oil, engineered to maximize fuel savings. ZIC X7 FE's unique friction modifiers maximize your engine's performance for dynamic driving. ZIC X7 FE is formulated with VHVI Technology for lower oil consumption and longer drain intervals. ZIC X7 generates a strong oil film to protect your engine from wear. ZIC X7 FE is especially developed for hybrid vehicles requiring 0W grade engine oils.

RECOMMENDATIONS

- Recommended for Gasoline/CNG/LPG engines

TYPICAL PROPERTIES

SAE Grade	0W-20	0W-30	5W-20
Density, g/cm ³	0.8449	0.8430	0.8525
Kinematic Viscosity at 40°C, cSt	44.74	54.80	49.32
Kinematic Viscosity at 100°C, cSt	8.429	10.25	8.596
Viscosity Index	166	178	153
Total Base Number (TBN), mgKOH/g	7.95	8.05	8.00
Flash Point, °C	220	220	220
Pour Point, °C	-39	-39	-36
CCS, cP	6,100 (-35°C)	5,900 (-35°C)	5,700 (-30°C)
MRV, cP	31,000 (-40°C)	42,00 (-40°C)	30,000 (-35°C)