

ZIC M7 4T

MCO

SYNTHETIC MOTOR OIL FOR  
EXCELLENT PROTECTION AND  
A SMOOTH RIDE



SYNTHETIC  
SPECIFICATIONS  
- API SL; JASO MA2



GENERAL CHARACTERISTICS

- Excellent wear protection
- Excellent thermal and oxidation stability
- Great corrosion protection
- Longer engine life and longer life of valve train and bearing components

DESCRIPTION

ZIC M7 4T is designed to provide excellent engine protection for your engine, transmission and gears. It guarantees maximum power transfer and smooth shifting for high performance.

RECOMMENDATIONS

- Recommended for 4-stroke motorcycles

TYPICAL PROPERTIES

SAE Grade	10W-30	10W-40	20W-40
Density, g/cm <sup>3</sup>	0.8530	0.8540	0.8768
Kinematic Viscosity at 40°C, cSt	68.50	89.65	120.0
Kinematic Viscosity at 100°C, cSt	10.75	14.05	14.17
Viscosity Index	155	163	118
Total Base Number (TBN), mgKOH/g	5.70	5.84	5.63
Flash Point, °C	230	230	230
Pour Point, °C	-36	-33	-30
CCS, cP	4,000 (-25°C)	3,800 (-25°C)	6,500 (-15°C)
MRV, cP	12,500 (-30°C)	18,000 (-30°C)	16,000 (-20°C)